

AM 150 HH B DE – ePM₁₀ 50%,CC,HS

Series	Type	Options
AM	150	BP Bypass (standard)
		CC Comfort Cooling Module
		CP Condensate Pump
		ED Motor-driven Exhaust Air Damper
		EM Energy Meter
		ePM ₁₀ 50% Intake air filter ePM ₁₀ 50%
		ePM ₁ 55% Intake air filter ePM ₁ 55%
		ePM ₁ 80% Intake air filter ePM ₁ 80% *
		HS Heating Surface (Virtual Preheat Function and Comfort Heater Function)
		SD Motor-driven Intake Air Damper
		CO CO ₂ Sensor, wall mounted
		HY Hygostat, wall mounted, L *
		ICO CO ₂ Sensor, integrated (Analog)
		ICT CO ₂ /TVOC Sensor, integrated (Analog)
		IPIR Motion Sensor, integrated
		IT TVOC Sensor, integrated
		PIR Motion Sensor, wall mounted
		B1 BACnet™/IP
		B2 BACnet™ MS/TP
		K KNX® *
		L LON® *
		M MODBUS® RTU RS485
		AO Airmaster Airlinq® Online

Series	Type
AM	150
Model	
HH	Horizontal
HHL	Horizontal Left

Version	
1. Character	
B	Inlet Bottom
DI	Ducted Inlet
2. Character	
B	Extract Bottom
DE	Ducted Extract

*Special item